

# Atlas Copco Generators

Designed to perform, built to last.



## QAS 250 (60 Hz)



### Durability

- Rugged Zincor steel coated canopy.
- Mounted on rugged skids.
- Designed for extreme weather conditions.
- A standard sealed spillage-free frame, which will ensure that all fluids can be retained within the frame.

### Efficiency

- Increased up-time: carefully selected components and tested configuration.
- Genuine versatility: QAS 250 can power a wide variation of critical applications.
- Reduced cost of ownership: 500 hrs service intervals, efficient transport handling.
- Designed for easy servicing.

### Health, Safety and Environment

Atlas Copco's stringent manufacturing standards follow ISO 9001 quality assurance regulations. All components are produced and tested to exacting standards for optimum performance in the most demanding conditions.

*Atlas Copco*

# Technical Data

Model	QAS 250
Rated Standby Power	209 kW / 262 kVA
Rated Prime Power	190 kW / 238 kVA
Voltage Selections 3Ø	208 / 240 / 480
Amperage Capacity @ 120 volts 1Ø	2 x 630 amps
Amperage Capacity @ 240 volts 1Ø	630 amps
Amperage Capacity @ 208 volts 3Ø	630 amps
Amperage Capacity @ 240 volts 3Ø	577 amps
Amperage Capacity @ 480 volts 3Ø	290 amps
Sound Pressure Level@ 23 feet @ 75% load	71 dB(A)
Fuel Tank Capacity (w/trailer)	326 gal.
Fuel Consumption @ 75% load	10.7 gal/hr
Fuel Autonomy @ 75% load (w/trailer)	30 hr

Engine	John Deere
Model	6068HF485
Rated Speed	1800 rpm
Emission Compliance	EPA Tier III
Rated Output	226 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	6
Displacement	6.8 L
Engine Control	Electronic

Alternator	Mecc Alte
Model	ECO 38 3S/N
Degree Of Protection / Insulation Class	IP23 / H

Dimensions and Weight	
Dimensions Skid (L x W x H)	136.6 x 56.3 x 83.8 in.
Weight Skid Wet	8,907 lbs
Dimensions w/trailer (L x W x H)	198.1 x 90.1 x 108 in.
Weight - w/trailer Wet	13,289 lbs

Convenience Receptacles	
1 x 20 amp	125 volt GFCI duplex
2 x 50 amp	125 / 250 volt twist lock

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.

## Generator Features and Options Include

Multi-Voltage Selector Switch	●
Remote Start / Stop	●
Digital Control System	●
110% Fluid Containment	●
Oil Drain Pump	●
Skid-Mount	○
Battery Charger	○
Electronic Governor	●
Coolant Heater	●
Ball Coupling	○
Spare Tire	○
Rear Stabilizer Jacks	○
Tool Box	○
External Fuel Connections	●
4 Position Voltage Selector Switch	○
3 Position Voltage Selector Switch with 120/240 - 3Ø	○
	Option ○
	Standard ●



## Control Panel

A comprehensive instrument panel enables all key operating functions to be supervised without opening the canopy. Analog gauges provide at-a-glance monitoring. Protected by a tough transparent cover, the single panel provides easy start up and control of the generator. The panel also provides full system monitoring to ease operation.

## U.S. Sales/Distribution Center

Atlas Copco Compressors LLC  
 1800 Overview Drive  
 Rock Hill, SC 29730  
 Tel. 803-817-7438  
 Tel. 800-232-3234  
 Fax. 803-817-7450  
[www.atlascopco.us](http://www.atlascopco.us)

